


REC'D 16 MAR 2005

WIPO

PA 1283028



10/05/050897

THE UNITED STATES OF AMERICA

TO ALL TO WHOM THESE PRESENTS SHALL COME:

UNITED STATES DEPARTMENT OF COMMERCE

United States Patent and Trademark Office

February 11, 2005

THIS IS TO CERTIFY THAT ANNEXED HERETO IS A TRUE COPY FROM THE RECORDS OF THE UNITED STATES PATENT AND TRADEMARK OFFICE OF THOSE PAPERS OF THE BELOW IDENTIFIED PATENT APPLICATION THAT MET THE REQUIREMENTS TO BE GRANTED A FILING DATE UNDER 35 USC 111.


APPLICATION NUMBER: 60/553,749 ✓


FILING DATE: March 16, 2004 ✓

PRIORITY DOCUMENT


SUBMITTED OR TRANSMITTED IN
COMPLIANCE WITH RULE 17.1(a) OR (b)

By Authority of the
COMMISSIONER OF PATENTS AND TRADEMARKS




M. K. HAWKINS
Certifying Officer

031604


Please type a plus sign (+) inside this box → 

PTO/SB/16 (02-01)
Approved for use through 10/31/2002. OMB 0851-0032
Patent and Trademark Office, U.S. DEPARTMENT OF COMMERCE
Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it displays a valid OMB control number.

PROVISIONAL APPLICATION FOR PATENT COVER SHEET
This is a request for filing a PROVISIONAL APPLICATION FOR PATENT under 37 CFR 1.53 (c).

Express Mail Label No. EV 312 068 272

Date of Deposit: March 16, 2004

INVENTOR(S)					
Given Name (first and middle [if any])	Family Name or Surname	Residence (City and either State or Foreign Country)			
Hans Duncan J.	ZOU ANDERSON	Windsor, NJ Sleepy Hollow, NY			
<input type="checkbox"/> Additional inventors are being named on the _____ separately numbered sheets attached hereto					
TITLE OF THE INVENTION (280 characters max)					
HIGH BRIGHTNESS ILLUMINATION DEVICE WITH SOLID STATE LIGHT SOURCE					
CORRESPONDENCE ADDRESS					
Direct all correspondence to:					
<input checked="" type="checkbox"/> Customer Number		24737		→ *24737* 	
OR Type Customer Number here					
<input checked="" type="checkbox"/> Firm or Individual Name		U. S. PHILIPS CORPORATION			
Address		P. O. BOX 3001			
Address					
City	BRIARCLIFF MANOR	State	NY	ZIP	10510
Country	USA	Telephone	(914) 945-6000	Fax	(914) 332-0615
ENCLOSED APPLICATION PARTS (check all that apply)					
<input checked="" type="checkbox"/> Specification Number of Pages		14		<input type="checkbox"/> CD(s), Number _____	
X Drawing(s) Number of Sheets		6		Other (specify) _____	
<input type="checkbox"/> Application Data Sheet. See 37 CFR 1.76					
METHOD OF PAYMENT OF FILING FEES FOR THIS PROVISIONAL APPLICATION FOR PATENT (check one)					
<input type="checkbox"/> Applicant claims small entity status. See 37 CFR 1.27.					
<input type="checkbox"/> A check or money order is enclosed to cover the filing fees					
FILING FEE AMOUNT (\$)					
<input checked="" type="checkbox"/> The Commissioner is hereby authorized to charge filing fees or credit any overpayment to Deposit Account Number:		14-1270		160.00	
<input type="checkbox"/> Payment by credit card. Form PTO-2038 is attached.					
The invention was made by an agency of the United States Government or under a contract with an agency of the United States Government.					
<input checked="" type="checkbox"/> No.					
<input type="checkbox"/> Yes, the name of the U.S. Government agency and the Government contract number are: _____					

Respectfully submitted,
SIGNATURE

Date March 16, 2004

TYPED or PRINTED NAME

ERIC M. BRAM

REGISTRATION NO.: 37,285
(if appropriate)

Docket Number: US 040151

TELEPHONE

(914) 333-9635

USE ONLY FOR FILING A PROVISIONAL APPLICATION FOR PATENT

This collection of information is required by 37 CFR 1.51. The information is used by the public to file (and by the PTO to process) a provisional application. Confidentiality is governed by 35 U.S.C. 122 and 37 CFR 1.14. This collection is estimated to take 8 hours to complete, including gathering, preparing, and submitting the complete provisional application to the PTO. Time will vary depending upon the individual case. Any comments on the amount of time you require to complete this form and/or suggestions for reducing this burden, should be sent to the Chief Information Officer, U.S. Patent and Trademark Office, U.S. Department of Commerce.

19587 U.S. PTO
60/553749

031604

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

In re Application of

Atty. Docket

HANS ZOU ET AL

US040151

Serial No.

Filed: CONCURRENTLY

Title: HIGH BRIGHTNESS ILLUMINATION DEVICE WITH SOLID
STATE LIGHT SOURCE

Commissioner for Patents
Alexandria, VA 22313

APPOINTMENT OF ASSOCIATES

Sir:

The undersigned Attorney of Record hereby revokes all
prior appointments (if any) of Associate Attorney(s) or Agent(s) in
the above-captioned case and appoints:


ERIC M. BRAM

(Registration No. 37,285)

c/o U.S. PHILIPS CORPORATION, Intellectual Property Department,
P.O. BOX 3001, Briarcliff Manor NY 10510, his Associate
Attorney(s)/Agent(s) with all the usual powers to prosecute the
above-identified application and any division or continuation
thereof, to make alterations and amendments therein, and to
transact all business in the Patent and Trademark Office connected
therewith.

ALL CORRESPONDENCE CONCERNING THIS APPLICATION AND THE
LETTERS PATENT WHEN GRANTED SHOULD BE ADDRESSED TO THE UNDERSIGNED.
ATTORNEY OF RECORD.

Respectfully,



Michael E. Marion, Reg: 32,266
Attorney of Record

HIGH BRIGHTNESS ILLUMINATION DEVICE WITH INCOHERENT SOLID STATE LIGHT SOURCE

5

This invention pertains to the field of light sources for display devices, and in particular, illumination devices based on incoherent solid state light sources.

10 Illumination devices based on solid state devices, such as light emitting diodes (LEDs), have many desirable characteristics. Accordingly, it has been desired to adapt such illumination devices for use in projection displays based on a micro-display device, such as a liquid crystal on silicon (LCOS) imaging device. For example, in comparison to existing projection display light sources such as ultra high pressure (UHP) arc lamps, etc., LED-based illumination devices have a superior lifetime, produce a more pure color with
15 little or no undesired ultraviolet or infrared light, and operate with DC power at reasonable voltage levels. Also, LED-based illumination devices can be intensity-modulated, which makes them well-suited for frame sequential color illumination schemes. Additionally, the use of separate color LED light sources enables compact color management architectures to be created.

20 However, a critical requirement for an illumination system for a projection display system is a high brightness level. Unfortunately, the brightness levels of existing LED-based illumination devices are substantially less than the brightness levels of conventional UHP arc lamps. Therefore, for example, when existing LED-based illumination devices are used in projection display systems, the screen size that can be illuminated and still
25 provide an acceptably bright image is limited. Although efforts are continually undertaken to improve things such as the base materials used for fabricating LED light sources, heat sinking of LED light sources, etc., thus far these efforts have produced limited results.

Accordingly, it would be desirable to provide an illumination device using an incoherent solid state light source, which has a high brightness level. It would further be
30 desirable to provide an improved illumination device suitable for use in projection display systems. The present invention is directed to addressing one or more of the preceding concerns.

In one aspect of the invention, an illumination device comprises an incoherent solid state light source adapted to emit light over at least one light emission surface and having a total light emission surface area S_0 ; and a reflective cavity having an entrance aperture for receiving the light from the incoherent solid state light source and a light extraction aperture for outputting the light from the incoherent solid state light source, wherein a surface area S_1 of the light extraction aperture of the reflective cavity is smaller than S_0 .

In another aspect of the invention, an illumination device comprises an incoherent solid state light source adapted to emit light over at least one light emission surface, and having a total light emission surface area S_0 ; and a reflective layer disposed directly on and covering the incoherent solid state light source and having therein an opening for outputting the light from the incoherent solid state light source, wherein an area S_1 of the opening of the reflective layer is smaller than S_0 .

In another aspect of the invention, an illumination device comprises an incoherent solid state light source adapted to emit light over a at least one light emission surface, and having a total light emission surface area S_0 ; a light circulation device including at least one light receiving surface adapted to receive the light from the incoherent solid state light source, and a light extraction area having a second surface area S_1 ; and means for extracting the light from the light circulation device at the light extraction area, wherein S_1 is smaller than S_0 .

FIG. 1 shows a first embodiment of an illumination device according to one or more aspects of the present invention;

FIG. 2 shows a second embodiment of an illumination device according to one or more aspects of the present invention;

FIG. 3 shows a third embodiment of an illumination device according to one or more aspects of the present invention;

FIG. 4 shows a fourth embodiment of an illumination device according to one or more aspects of the present invention;

FIG. 5 shows a fifth embodiment of an illumination device according to one or more aspects of the present invention;

FIG. 6 shows a sixth embodiment of an illumination device according to one or more aspects of the present invention.

As used herein, the term "incoherent solid state light source" refers to an arrangement of one or more incoherent solid state devices (e.g., light emitting diodes; organic light emitting diodes; etc.) emitting light, such as a large surface area LED chip, an LED array, or one or more extended linear LEDs.

FIG. 1 shows a first embodiment 100 of an illumination device.

The illumination device 100 of FIG. 1 includes an incoherent solid state light source 110 and a reflective cavity 120 having an entrance aperture 122 and a light extraction aperture 124.

The incoherent solid state light source 110 may comprise a single extended or large surface area light emitting diode (LED) chip, or an array of smaller LEDs. The incoherent solid state light source 110 emits light over a light emission surface 112 having a total light emission surface area S_0 . As a solid state device, incoherent solid state light source 110 may be easily electronically controlled (e.g., switched on and off, intensity modulated, etc.) as desired to control the light output of the illumination device 100.

Meanwhile, the reflective cavity 120 is a light circulation device. The inside of the top surface 125 and the sidewalls 127 of the reflective cavity 120 are highly reflective at the wavelengths of the light emitted by the incoherent solid state light source 110. For example, the inside surfaces of the reflective cavity 120 may be coated with a highly reflective mirror coating 129. This may be a metallic coating, a dielectric multilayer coating, or even achieved by total internal reflection. Alternatively, the material used to form the structure of the reflective cavity 120 may itself be a highly reflective material. Furthermore, the reflective cavity 120 is disposed such that the entrance aperture 122 covers the light emission surface 112 of the incoherent solid state light source 110.

Significantly, the surface area S_1 of the light extraction aperture 124 of the reflective cavity 120 is substantially smaller than the surface area S_0 of the light emission surface 112 of the incoherent solid state light source 110.

The illumination device 100 operates as follows. Light emitted by the incoherent solid state light source 110 at the light emission surface 112 enters the reflective cavity 120 through the entrance aperture 122. Some of the light will initially impinge on the light extraction aperture 124 of the reflective cavity 120 and thereby exit the reflective cavity

120. The remainder of the light emitted by the incoherent solid state light source 110 will be confined within the cavity by the reflective inside surfaces. The light will bounce around within the reflective cavity 120 until it finally impinges on the light extraction aperture 124 of the reflective cavity 120 and thereby exits the reflective cavity 120. Hence, light exiting through the light extraction aperture 124 of the reflective cavity 120 includes contributions from the light from the normal emitting area of the incoherent solid state light source 110 that directly impinges on the light extraction aperture 124, and contributions from the rest of the light emission surface 112 of the incoherent solid state light source 110. Accordingly, the apparent brightness of the light has been increased by distributing it over a smaller area.

Alternatively, the highly reflective mirror coating 129 can be provided directly on the light emission surface 112 of the incoherent solid state light source 110 without any cavity structure. The highly reflective mirror coating 129 is provided with an opening for the light extraction aperture 124, located above a small area of the light emission surface 112 of the incoherent solid state light source 110. Beneficially, an index matching material such as a fluid or gel is provided on the small area of the light emission surface 112 which is not covered by the highly reflective mirror coating 129. Also, LED materials are normally highly refractive and support total internal reflection at high angles, especially with an air cladding. Accordingly, in another alternative arrangement, the incoherent solid state light source 110 comprises a large surface area LED chip whose light emitting surface 112 is clad with air, except in a small area of the light emitting surface 112 where an index matching material such as a fluid or gel is provided.

Beneficially, the shape of the light extraction aperture 124 can be arbitrarily chosen to match a desired shape of a light beam to be produced by the illumination device 100. For example, when the illumination device 100 is to be used to illuminate a rectangular micro-display device (e.g., and LCOS imaging device) for a widescreen projection display system, then the aspect ratio of the light extraction aperture 124 can be set to 16:9.

FIG. 2 shows a second embodiment 200 of an illumination device.

The illumination device 200 of FIG. 2 includes an incoherent solid state light source 210, a light guide 220, and a light extraction device 230.

The incoherent solid state light source 210 is arranged with a light emission surface 212 disposed adjacent to a light receiving surface 222 of the light guide 220 which is

adapted to receive the light from the incoherent solid state light source 210. The light extraction device 230 is arranged to be optically coupled to the light guide 220 via a light extraction area 224 of the light guide 220 having an extraction surface area S_1 .

The incoherent solid state light source 210 may comprises a large number of individual LEDs configured in one or more arrays, or a fewer number of large surface area or extended linear LEDs. Beneficially, the LED-based illumination device 200 the incoherent solid state light source 210 may be physically separated into two or more large surface area LEDs or LED arrays each having a different light emission surface 212 disposed adjacent to a corresponding light receiving surface 222 of the light guide 220. The light emission surface(s) 212 of the incoherent solid state light source 210 has a total light emission surface area S_0 .

Beneficially, the incoherent solid state light source 210 provides collimated light to the light guide 220.

The light guide 220 is a light circulation device. Beneficially, the light guide 220 is fabricated of a low-loss, solid, transparent material with a refractive index $N > 1$. Optionally, the light guide 220 may be hollow. On exterior surfaces of the light guide 220 where total internal reflection (TIR) is not supported, a highly reflective material 229 is provided. The highly reflective material 229 may be Spectralon, Teflon, or another suitable material.

Beneficially, the light extraction device 230 is a light-collimating structure such as a compound parabolic collimator (CPC), or a prismatic optical component that extracts the light from the light guide 220. Beneficially, light extraction device 230 is fabricated of a material which is refractive index-matched to the solid transparent material of the light guide 220.

Significantly, the surface area S_1 of the light extraction area 224 of the light guide 220 is substantially smaller than the total surface area S_0 of the light emission surface(s) 212 of the incoherent solid state light source(s) 210.

The illumination device 200 operates as follows. Light emitted by the incoherent solid state light source 210, at the light emission surface(s) 212, enters the light guide 220 at one or more corresponding light receiving surface(s) 222. Some of the light will initially be coupled out of the light guide 220 through the light extraction area 224 and emerge as a collimated light beam at the light extraction device 230. The remainder of the light emitted

by the incoherent solid state light source 210 will be confined within the light guide 220 by TIR and by the highly reflective material 229 provided on surfaces of the light guide 220 that do not support TIR. The light will bounce around within the light guide 220 until it is finally coupled out of the light guide 220 through the light extraction area 224 and emerges
5 as a collimated light beam at the light extraction device 230. Hence, light exiting through light extraction device 230 includes contributions from the light from the total area of the light emission surface(s) 212 of the incoherent solid state light source 210. Accordingly, the apparent brightness of the light has been increased by collimating and distributing it over a smaller area.

10 In similarity to the embodiment of FIG. 1, the light extraction aperture 224 can be arbitrarily chosen to match a desired shape of a light beam to be produced by the illumination device 200. For example, when the illumination device 200 is to be used to illuminate a rectangular micro-display device (e.g., and LCOS imaging device) for a widescreen projection display system, then the aspect ratio of the light extraction aperture
15 224 can be set to 16:9.

In some applications, such as when an illumination device is to be used to illuminate a rectangular micro-display device (e.g., and LCOS imaging device) for a widescreen projection display system, it is desired or necessary to produce a polarized (i.e., linearly polarized) light beam. FIG. 3 shows a third embodiment 300 of an illumination
20 device that can produce and output a polarized light beam.

The illumination device 300 is similar to the illumination device 200, except for the following differences. First, in place of the highly reflective material 229, diffusing reflectors 329 are provided on exterior surfaces of the light guide 220 where total internal reflection (TIR) is not supported. Second, a reflective polarizer 340 is provided between
25 the light guide 220 and the light extraction device 230. The reflective polarizer 340 may comprise a wire grid polarizer, a cholesteric polarizer, or a highly anisotropic layer of material that reflects light having one polarization (e.g., through TIR), and transmits light having the orthogonal polarization.

As before, the light guide 220 is a light circulation device, and the surface area S_1 of
30 the light extraction area 224 of the light guide 220 is substantially smaller than the total surface area S_0 of the light emission surface(s) 212 of the incoherent solid state light source 210.

The illumination device 300 also operates similarly to the illumination device 200, except with the following differences.

5 The light from the incoherent solid state light source 210 is assumed to be initially unpolarized. Light that reaches the light extraction area 224 of the light guide 220 is passed to the reflective polarizer 340. A part of the light that has the desired polarization passes through the reflective polarizer 340 and is coupled into the light extraction device 230 as a collimated, polarized light beam. The remainder of the light that does not have the desired polarization is reflected by the reflective polarizer 340 back into light guide 220. Meanwhile, the diffusing reflectors 339 operate to change the polarization of the light
10 reflected back into the light guide 220 so that it has components having the correct polarization for passing through the reflective polarizer 340. So, in the illumination device 300 the light from the incoherent solid state light source circulates within the low-loss light guide 220 until it reaches the light extraction area 224 with the correct polarization to pass through the reflective polarizer 340 and into the light extraction device 230.

15 Accordingly, the apparent brightness of the light has been increased by collimating and distributing it over a smaller area, and the light has been correctly polarized as desired without discarding the portion of the light that was originally of the wrong polarization.

20 In an alternative arrangement, the diffusing reflector(s) 339 are replaced with specular reflector(s) 339 disposed on exterior surfaces of the light guide 220 where total internal reflection (TIR) is not supported, and a quarter wavelength foil 345 is provided in an optical path between each specular reflector 339 and the reflective polarizer. Here, the axis of the quarter wavelength foil makes an angle of about 45 degrees with the transmission direction of the reflective polarizer 340. The quarter wavelength foil 345 may
25 be provided between the light guide 220 and the reflective polarizer 340, or between each specular reflector 339 and the corresponding sidewall of the light guide 220.

FIG. 4 shows a top view of a fourth embodiment 400 of an illumination device that can produce and output a polarized light beam.

30 The illumination device 400 is similar to the illumination device 200, with a large area LED chip, or LED array, disposed along each of the four sidewalls of the light guide 220. The highly reflective material 239 covers any areas of the sidewalls where the LED(s) are not arranged. In contrast to the illumination device 200, in the illumination

device 400 the light guide 220 is provided on one surface with a light extraction device 450 comprising light extraction and collimation optics.

The operation of the illumination device 400 is the same as that of the illumination device 200.

5 FIG. 4 illustrates that the achievable ultimate brightness of such an illumination device can be extremely high if a sufficiently large light guide is employed, and if an LED or LED array having a sufficiently large light emission surface area is coupled to the light guide. The final light output brightness is proportional to the ratio of the total surface area S_0 of the light emission surface of the incoherent solid state light source, to the surface area
10 S_1 of the extraction area of the light guide where the light extraction device is coupled. Additionally, the fraction of light that is out-coupled from the incoherent solid state light source (i.e., the coupling efficiency) also determines the integrated output brightness and should be maximized.

FIG. 5 shows a fifth embodiment 500 of an illumination device.

15 The illumination device 500 is similar to the illumination device 200, except for the following differences.

In the illumination device 500, the cross-section of the light guide 220 in planes parallel to the light receiving surface(s) 222 (sidewalls) to which the incoherent solid state light source 210 is coupled, varies in size. That is, the cross-section of the light guide 220
20 is "thicker" in some areas than in others. Specifically, the cross-section of a portion of the light guide 220 close to the light extraction area 224 is smaller than in other areas of the light guide 220. The reduced cross-section near the light extraction area 224 increases the chances of single-path light extraction, and minimizes the reflection loss for the retro-reflected light rays. Therefore the light-coupling efficiency of the light guide 220 is
25 increased.

In some applications, such as when an illumination device is to be used to illuminate a rectangular micro-display device (e.g., and LCOS imaging device) for a projection display system, it is desired or necessary to produce a light beam that can have different colors. FIG. 6 shows a sixth embodiment 600 of an illumination device that can
30 output light having different colors.

The illumination device 600 includes two different incoherent solid state light sources 210 emitting light having two different spectral colors (e.g., red and blue).

However, it is understood that more than two incoherent solid state light sources 210 could be employed having more than two colors, and colors other than red and blue are of course possible.

In addition to the components previously described above with respect to FIG. 2, the illumination device 600 includes two dichroic filters 660, each disposed between the light emission surface 212 of a corresponding incoherent solid state light source 210, and the corresponding light receiving surface 222 of the light guide 220. Each dichroic filter 660 transmits light having a first color corresponding to the color of the light emitted from the adjacent incoherent solid state light source 210, and reflects light having the other wavelengths of the light produced by the other incoherent solid state light sources 210 coupled into the light guide 220. Each incoherent solid state light source 210 may be individually electronically controlled (e.g., switched on and off, intensity modulated, etc.) to provide full color control of the collimated light beam at the light extraction device 230.

While embodiments are disclosed herein, many variations are possible which remain within the concept and scope of the invention. For example,. Such variations would become clear to one of ordinary skill in the art after inspection of the specification, drawings and claims herein. The invention therefore is not to be restricted except within the spirit and scope of the appended claims.

CLAIMS

1. An illumination device (100), comprising:
an incoherent solid state light source (110) adapted to emit light over at least one light emission surface (112) and having a total light emission surface area S_0 ; and
a reflective cavity (120) having an entrance aperture (122) adapted to receive the light from the incoherent solid state light source (110) and a light extraction aperture (124) adapted to output the light from the incoherent solid state light source (110),
wherein a surface area S_1 of the light extraction aperture (124) of the reflective cavity (120) is smaller than the surface area S_0 .
2. The illumination device (100) of claim 1, wherein the incoherent solid state light source (210) consists of a single extended LED.
3. The illumination device (100) of claim 1, wherein the incoherent solid state light source (210) comprises an array of LEDs.
4. The illumination device (100) of claim 1, wherein the light extraction aperture has a rectangular shape and an aspect ratio of 16:9.
5. An illumination device (100), comprising:
an incoherent solid state light source (110) adapted to emit light over at least one light emission surface (112) and having a total light emission surface area S_0 ; and
a reflective layer (129) disposed directly on and covering the incoherent solid state light source (110) and having therein an opening (124) for outputting the light from the incoherent solid state light source (110),
wherein a surface area S_1 of the opening (124) of the reflective layer (129) is smaller than the surface area S_0 .

6. The illumination device (100) of claim 5, further comprising a refractive index matching material disposed on an area of the first surface that is not covered with the reflective layer.
7. The illumination device (100) of claim 5, wherein the opening has a rectangular shape and an aspect ratio of 16:9.
8. An illumination device (200, 300, 400, 500, 600), comprising:
 - an incoherent solid state light source (210) adapted to emit light over at least one light emission surface (212) and having a total light emission surface area S_0 ;
 - a light circulation device (220) including
 - at least one light receiving surface (222) adapted to receive the light from the incoherent solid state light source (210), and
 - a light extraction area (224) having a surface area S_1 ; and
 - light extraction means (230) for extracting the light from the light circulation device (220) at the light extraction area (224),
 - wherein S_1 is smaller than S_0 .
9. The illumination device (200, 300, 400, 500, 600) of claim 8, wherein the light circulation device (220) comprises a solid light guide.
10. The illumination device (200, 300, 400, 500, 600) of claim 9, wherein the light circulation device (220) further comprises a reflective material disposed on a surface of the light guide which does not support total internal reflection.
11. The illumination device (200, 300, 400, 500, 600) of claim 8, wherein the light circulation device (220) comprises a hollow cavity.
12. The illumination device (200, 300, 400, 500, 600) of claim 8, wherein the light extraction means (230) comprises a light collimating structure.

13. The illumination device (200, 300, 500, 600) of claim 8, wherein the light extraction means (230) comprises a compound parabolic collimator.

14. The illumination device (400) of claim 8, wherein the light extraction means (450) comprises a prismatic optical component.

15. The illumination device (300) of claim 8, further comprising a reflective polarizer (340) disposed in an optical path between the light extraction area (224) and the light extraction means (230),

wherein the light circulation device (220) includes at least one diffusing reflector (339) disposed at a sidewall thereof.

16. The illumination device (300) of claim 8, wherein the light circulation device (220) includes at least one specular reflector (339) disposed at a sidewall thereof, said illumination device (300) further comprising:

a reflective polarizer (340) disposed in an optical path between the light extraction area (224) and the light extraction means (230); and

a quarter wavelength foil (345) in an optical path between the specular reflector (339) and the reflective polarizer (340).

17. The illumination device (400) of claim 8, wherein the light circulation device (220) includes at least two light receiving surfaces (222) and the incoherent solid state light source 210 includes at least two light-emitting components, each light-emitting component being disposed adjacent to and confronting a corresponding one of the light receiving surfaces (222).

18. The illumination device (500) of claim 8, wherein the light circulation device (220) has a cross-section who thickness is less near the light extraction area (224) than at the light receiving surface (222).

19. The illumination device (600) of claim 8, further comprising:

a second incoherent solid state light source adapted to emit light over at least a second light emission surface (212),

wherein the light circulation device (220) includes at least a second light receiving surface (222) adapted to receive the light from the second incoherent solid state light source (210), and

wherein the two incoherent solid state light sources each emit light having a different spectral color.

20. The illumination device (100) of claim 8, wherein the incoherent solid state light source (210) consists of a single extended LED.

ABSTRACT

- 5 An illumination light source includes an incoherent solid state light source adapted to emit light over at least one light emission surface and having a total light emission surface area S_0 ; a light circulation device including at least one light receiving surface adapted to receive the light from the incoherent solid state light source, and a light extraction area having a first surface area S_1 ; and a light extraction device for extracting the
- 10 light from the light circulation device at the light extraction area, wherein $S_1 < S_0$. Accordingly, the apparent brightness of the light is increased by distributing it over a smaller area.

100




FIG. 1

200




FIG. 2

300




FIG. 3

400




FIG. 4

500




FIG. 5

600




FIG. 6